


ULTRATREX AT200ER-V2

UTX, YOUR TRUSTED PARTNER IN SHALLOW DREDGING EQUIPMENT









ULTRATREX MACHINERY SDN. BHD.

Email: marketing@ultratrex.com.my



INTRODUCTION

Ultratrex amphibious excavator is an excavator that can travel and work safely and effectively on soft terrain such as swamp, wet land and shallow water. The well designed amphibious hydraulic undercarriage has ultra-low ground pressure and unparalleled mobility to work on soft terrains and swamps area



FEATURES

Track plates

- Ultra High Molecular Weight Polyethylene (UHMWPE)
- High strength and quality material.
- 10000 Hours warranty

Gear Rack Spud

- High precision rack gear teeth and pitch
- Robust design to give stabilization while digging in deeper water.

Grease Tensioner System

- Easire method chain tensioning system rather than convensional system by using spanner
- Using grease to move chain tensioning cylinder

Amphibious Undercarriage construction

- Anti corrosion plate SMA 490
- 3 independent water compartments
- Reinforce bottom area

Track Chains

- Triple strands
- Track chain pitch : 152.4 mm
- Running on hardox AR400 wear plate

Amphibious Undercarriage Hydrostatic Drive

- Brand: Bonfiglioli
- Origin: Italy
- Integrated hydraulic 2 speed motors
- Output torque: 3059kgf.m

TÜV

CERT NO.: TUV 100-01-2043 ISO 9001:2015




APPLICATION

- Swamp land clearing at mining, plantation and forest area.
- Deepening of canal, river channel and river mouth.
- Building bund for flood prevention and reclamation
- Sludge clearing of lakes, ponds and water reservoir
- Digging trenches for oil and gas piping installation
- Transporting and clearing land slide and flood hit area
- Swamps and wetlands construction
- Road construction through wetland.




TECHNICAL SPECIFICATION

EXTEND POSITION:



BASE MACHINE TOTAL WEIGHT FLOAT CAPACITY 20 TON CLASS 32000 Kg 40 m3



ITEM		UNIT	VALUE
TRAVEL SPEED	HI	km/h	3.6
	LO	km/h	2.3
MAXIMUM GRADIENT		•	30
WORK EQUIPMENT	BOOM LENGTH	mm	7750
	ARM LENGTH	mm	5150
	BUCKET CAPACITY	m3	0.5
WORKING RANGE	a. MAX. DIGGING HEIGHT	mm	14360
	b. MAX. DUMPING HEIGHT	mm	12260
	c. MAX. DIGGING DEPTH	mm	8250
	d. MAX. DIGGING REACH	mm	13500
	e. MAX DIGGING REACH ON GROUND	mm	13250
	f. TOTAL LENGHT DURING PARKING	mm	13045
DIMENSIONS	A. TRACK GAUGE (FULLY RETRACTED)	mm	2760
	A1. TRACK GAUGE (FULLY EXTENDED)	mm	4020
	B. TRACK LENGTH	mm	9375
	C. DISTANCE BETWEEN IDLER & SPROCKET	mm	8660
	D. TRACK LENGTH ON HARD GROUND	mm	5700
	D1. TRACK LENGTH ON SOFT GROUND	mm	7735
	E. WIDTH TRACK SHOE	mm	1590
	E1. WIDTH FLOAT	mm	1620
	F. DISTANCE BETWEEN SHOE INSIDE (FULLY RETRACTED)	mm	1170
	F1. DISTANCE BETWEEN SHOE INSIDE (FULLY EXTENDED)	mm	2440
	G. OVERALL MACHINE WIDTH (FULLY RETRACTED)	mm	4575
	G1. OVERALL MACHINE WIDTH (FULLY EXTENDED)	mm	5815
	H. OVERALL MACHINE HEIGHT	mm	4050
	I. GROUND CLEARANCE (COUNTERWEIGHT)	mm	2215
	J. MIN. GROUND CLEARANCE	mm	1250
	K. SHOE SETTING HEIGHT	mm	2030
	L. CRAWLER HEIGHT	mm	2215
	M. WATER LINE LEVEL	mm	1620
	N. MIN SWING RADIUS	mm	2750
	O. CABIN WIDTH	mm	2900


GROUND PRESSURE 0.18 Kg/cm2

MAXIMUM TORQUE 3059 Kgf.m

FLOAT CAPACITY/ TOTAL WEIGHT

1.25 m3/ton

RETRACT POSITION:



- * Specification are subject to change without prior notice
- * All dimensions are without side pontoon and spud
- * Dimension are based on 13.5 m long reach arm and 0.5m3 GP bucket

ULTRATREX MACHINERY SDN. BHD.



ULTRATREX MACHINERY SDN. BHD.

TEL:+607 355 7777 FAX:+607 351 0229

HP:+6016 772 0584

E-MAIL: marketing@ultratrex.com.my

PLO 229, JALAN KENCANA MAS 2, KAWASAN PERINDUSTRIAN TEBRAU 3, 81100 JOHOR BAHRU, JOHOR, MALAYSIA.